Specifications



Photo is representative

Eaton DILM40(24V60HZ)

Eaton XT IEC contactor, 40A,24 Vac, 60 Hz, 0NO-0NC, 40A, Frame D, 55 mm, 60 Hz, 3, 7.5/ 10, 15, 30, 40 (1/3PH @120, 240/208, 240, 480, 600 V), Three-pole, Non-reversing, , Screw terminals, FVNR, 18.5 kW

General specifications	
PRODUCT NAME	Eaton XT IEC contactor
CATALOG NUMBER	DILM40(24V60HZ)
EAN	4015082777579
PRODUCT LENGTH/DEPTH	2.2 in
PRODUCT HEIGHT	4.5 in
PRODUCT WIDTH	5.2 in
PRODUCT WEIGHT	1.98 lb
WARRANTY	1 year
COMPLIANCES	CE Marked RoHS Compliant
CERTIFICATIONS	CSA Certified EN 60947 IEC 60947 UL Listed
CATALOG NOTES	Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)
PRODUCT TYPE	Contactors

Powering Business Worldwide

Product specifications

AMPERAGE RATING	40A
HP RATING - MAX	3, 7.5/ 10, 15, 30, 40 (1/3PH @120,240/208,240,480,600 V)
NUMBER OF POLES	Three-pole
TYPE	Full voltage non-reversing contactor
FREQUENCY RATING	60 Hz
FRAME SIZE	55 mm
TERMINALS	Screw terminals
COIL	24 Vac 60 Hz
COIL VOLTAGE	24 Vac, 60 Hz
CONTACT CONFIGURATION	0 NO, 0 NC
CONTINUOUS AMPERE RATING	40 A
SERIES	XT IEC
OPERATION	Non-reversing
POWER CONSUMPTION	18.5 kW

Resources

SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - DILM40(24V60HZ)

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.