Specifications



Photo is representative

Eaton XTCE040D00F

Eaton XT IEC contactor, 40A, 230 Vac, 50 Hz, 0NO-0NC, 40A, Frame D, 55 mm, 50 Hz, 3, 5, 7.5/ 10, 15, 30, 40 hp (1/3PH @115, 200, 230/200, 230, 460, 575 V), Three-pole, Screw terminals, Full voltage non-reversing contactor

General specifications	
PRODUCT NAME	Eaton XT IEC contactor
CATALOG NUMBER	XTCE040D00F
UPC	782116486298
PRODUCT LENGTH/DEPTH	2.244 in
PRODUCT HEIGHT	5.945 in
PRODUCT WIDTH	4.567 in
PRODUCT WEIGHT	2.4 lb
WARRANTY	1 year
COMPLIANCES	RoHS Compliant CE Marked
CERTIFICATIONS	IEC 60947 EN 60947 UL Listed CSA Certified
CATALOG NOTES	Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)
PRODUCT TYPE	Contactors

Powering Business Worldwide

Product specifications

AMPERAGE RATING	40A
HP RATING - MAX	3, 5, 7.5/ 10, 15, 30, 40 hp (1/3PH @115,200,230/200,230,460,575 V)
NUMBER OF POLES	Three-pole
TYPE	Full voltage non-reversing contactor
FREQUENCY RATING	50 Hz
FRAME SIZE	55 mm
TERMINALS	Screw terminals
COIL	230 Vac, 50 Hz
COIL VOLTAGE	230 Vac, 50 Hz
CONTACT CONFIGURATION	0 NO, 0 NC
CONTINUOUS AMPERE RATING	40 A
SERIES	XT IEC
OPERATION	Non-reversing

Resources

CATALOGS	Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - XTCE040D00F

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.